


# WDR Bullet Camera

**1/3" COLOR CCD Super High Resolution w/ 2.5~10mm Auto Iris Lens**

## CM259EZ-WDR

- \* 1/3" COLOR Wide Dynamic dual scan CCD High Resolution
- \* 620TVL 0.001 Low Lux
- \* Day / Night IR -Cut Control
- \* Super (SDNR) Digital Noise Reduction
- \* Easily Adjustable 2.5~10mm Varifocal
- \* OSD Easy Setup
- \* DC 12V 500mA



Cable with OSD Control Button

### ■ Specification

Model No.	CM259EZ-WDR	
Sensor	1/3 inch, COLOR DS CCD	
Total Pixels	811(H) x 508(V)	795(H) x 595(V)
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2:1 Interlace	2:1 Interlace
Synchronization	Internal / Line Lock	
O.S.D	Available	
Dynamic Range	52dB(x128)	
Backlight Compensation	WDR / BLC / OFF Selectable	
Resolution	COLOR : 620 TV Lines (Typ.)	
S/N (Y signal)	52 dB (AGC Off, Weight ON)	
Min. illumination	Color Mode : 0.003 (0.6) Lux (Sens-up Off) B/W Mode : 0.0001 (0.1) Lux (Sens-up Off)	
White Balance	ATW/AWC/Manual/Outdoor(1800 ° K ~ 10,500 ° K)Indoor(4500 ° K ~ 8,500 ° K)	
Electronic shutter speed	1/60sec ~ 1/120,000sec	1/50sec ~ 1/120,000sec
Sense-up	AUTO/FIXED/OFF (selectable limit x2 ~ x512)	
Gain Control	LOW,MIDDLE,HIGH,OFF Selectable	
3D-DNR	OFF/ON(1~ 63 Level Adjustable)	
Motion Detection	ON/OFF (8 Zone, ALARM Output))	
PRIVACY	ON/OFF (8 Zone)	
MIRROR(H-REV)	ON/OFF	
FLIP(V-REV)	ON/OFF	
Freeze	ON/OFF	
SHARPNESS	ON/OFF (Level Adjustable)	
D&N Selection	COLOR/Black&White/AUTO/EXT	
STABILIZER	ON/OFF	
Digital Zoom	ON(x6)/OFF	
Blemish Compensation	256 point(Even 128 Point, ODD 128 Point)	
IRIS Control	DC	
POWER	DC 12V ± 10%, Max. 2.0W	
Operating Temperature/Humidity	0-10℃ to +50℃ /30% to 80%RH	
Storage Temperature/Humidity	-20℃ to +60℃ /20% to 90%RH	
Dimension		
Weight		

\* Specifications are subject to change without notice

\*\* Designed in U.S.A.